



## CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Space Grey/Orange
CADRE	ALUXX SL aluminum, Overdrive 1½ - 1⅞" head tube, integrated KS18 kickstand mount
FOURCHE	RST Pulse 29 Air, 60mm travel, tapered steerer, lockout, 100x15 thru-axle
COMPOSANTS	
CINTRE	Giant Connect XC Riser
POTENCE	Giant Connect
TIGE DE SELLE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLE	Giant Contact Comfort, Upright
PÉDALES	Aluminum Platform
DÉRAILLEUR	
MANETTES	Shimano XT
DÉRAILLEUR AVANT	Shimano XT
DÉRAILLEUR ARRIÈRE	Shimano XT, 11-Speed, Shadow+
FREINS	Shimano BR-MT500, hydraulic disc, 180mm
LEVIERS DE FREIN	Shimano BL-MT500, i-spec II
CASSETTE	Shimano HG-M7000, 11-40T, 11-Speed
CHAÎNE	KMC e.11 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Forged Alloy minimal Q-factor, 36/48T
ROUES	
JANTES	Giant eX 2, Tubeless Ready, 700c aluminium, e-bike optimized
MOYEURS	Giant eTracker, sealed cartridge bearings [F] 15mm Thru-Axle [R] 135mm QR, e-bike optimized
RAYONS	Stainless steel
PNEUS	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready
EXTRAS	Giant EnergyPak 4A fast charger MIK system carrier top-deck
TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Sport, 80Nm powered by YAMAHA, 350% tuneable support
CAPTEURS	Giant PedalPlus 4-sensor technology
CONSOLE	Giant RideControl EVO, grip launch control with walk assist, on-board navigation, mini USB charger
BATTERIE	Giant EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion
ACCESSOIRES	
ECLAIRAGE	Axa BlueLine 50Lux Steady E6 front/Axa BlueLine Steady E6 rear
PORTE-BAGAGES	MIK rack. System bag & basket compatible

## CARACTÉRISTIQUES

- Giant SyncDrive Sport, 80Nm powered by YAMAHA
- Giant EnergyPak 500 lithium-ion battery
- Giant RideControl EVO display w/onboard navigation & smartphone connectivity
- Shimano Deore XT 22-speed drivetrain
- Tubeless tire for maximum puncture protection
- Color: Space Grey/Orange

Prix: 3 299 €

## GÉOMÉTRIE

CADRE	S	M	L	XL
Longueur de tube de selle (mm)	435	485	535	585
Angle de tube de selle	74,0°	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	570	590	610	630
Longueur du tube de direction (mm)	130	140	155	170
Angle du tube de direction	69,5°	69,5°	69,5°	69,5°
Déport de fourche (mm)	42	42	42	42
Trail (mm)	91	91	91	91
Empattement (mm)	1112	1121	1142	1163
Longueur fourche de pédalier (mm)	455	455	455	455
Hauteur du boîtier de pédalier (mm)	60	60	60	60
Stack (mm)	610	619	633	648
Reach (mm)	395	400	416	432
Hauteur en statique (mm)	745	775	808	844
Largeur de cintre (mm)	690	690	690	690
Longueur de potence (mm)	60	70	80	90
Longueur des manivelles (mm)	170	170	170	170
Diamètre des roues	700c	700c	700c	700c

Produits conformes aux exigences de sécurité (décret n°95-937). GIANT France se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles. Les prix sont librement fixés par les revendeurs Giant de ce fait ils n'apparaissent pas sur le site Internet.