

VALL-E+ 3 POWER



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COLORIS	True Blue/Magenta
CADRE	ALUXX aluminum, Overdrive 1½ - 1½" head tube, 141mm Boost QR, integrated KS18 kickstand mount
FOURCHE	SR Suntour XCM34 HLO 27,5+ 120mm travel, Tapered 1½ - 1½" steerer, lockout
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Connect TR
POTENCE	Giant Connect
TIGE DE SELLE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLE	Liv Contact, Forward
PÉDALES	Aluminum Platform
DÉRAILLEUR	
MANETTES	Shimano SL-M2000
DÉRAILLEUR AVANT	-
DÉRAILLEUR ARRIÈRE	Shimano Deore, 9-Speed
FREINS	Tektro HD-M285, hydraulic disc, 180mm
LEVIERS DE FREIN	Tektro HD-M285
CASSETTE	Shimano CS-HG201, 11-36T, 9-Speed
CHAÎNE	KMC e.9 Sport, e-bike optimized
PÉDALIER	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
ROUES	
PÉDALIER	N/A
JANTES	Giant AM 27.5, Tubeless ready, 30mm inner width, e-bike optimized
MOYEUX	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR, e-bike optimized
RAYONS	Stainless steel
PNEUS	Maxxis Forekaster 27.5x2.6, foldable, 60 TPI, EXO, Tubeless ready
EXTRAS	Giant EnergyPak 4A fast charger
TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Sport, 80Nm powered by YAMAHA
CAPTEURS	Giant PedalPlus 4-sensor technology
CONSOLE	Giant RideControl ONE, remote button
BATTERIE	Giant EnergyPak500, 36V 13.8Ah Rechargeable Lithium-Ion

CARACTÉRISTIQUES

- Giant SyncDrive Sport, 80Nm powered by YAMAHA
- Giant EnergyPak500 lithium-ion battery
- SR Suntour XCM 120mm suspension fork with lockout
- Shimano 9-speed drivetrain
- Hydraulic disc brakes
- Color: True Blue/Magenta

Prix: 2 299 €

GÉOMÉTRIE

CADRE	XS	S	M	L
Longueur de tube de selle (mm)	365	405	460	510
Angle de tube de selle	74,0°	73,5°	73,0°	73,0°
Longueur du tube supérieur (mm)	550	565	585	600
Longueur du tube de direction (mm)	110	115	135	150
Angle du tube de direction	68,0°	68,0°	68,0°	68,0°
Déport de fourche (mm)	42	42	42	42
Trail (mm)	100	100	100	100
Empattement (mm)	1116	1126	1142	1158
Longueur fourche de pédalier (mm)	475	475	475	475
Hauteur du boîtier de pédalier (mm)	50	50	50	50
Stack (mm)	612	617	635	649
Reach (mm)	374	382	390	401
Hauteur en statique (mm)	674	696	742	763
Largeur de cintre (mm)	690	690	750	750
Longueur de potence (mm)	50	50	60	70
Longueur des manivelles (mm)	170	170	170	170
Diamètre des roues	27.5+	27.5+	27.5+	27.5+

Produits conformes aux exigences de sécurité (décret n°95-937). GIANT France se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles. Les prix sont librement fixés par les revendeurs Giant de ce fait ils n'apparaissent pas sur le site Internet.